



ARCHITECTURAL SPECIFICATIONS

PLEASE REMEMBER YOU NEED TO COMPLETE AN ARCHITECTURAL REQUEST AND RECEIVE APPROVAL PRIOR TO STARTING WORK

WINDOWS

- **Brand:** Milgard Windows & Doors
- **Series:** Style Line - V250 Windows
- **Color:** White (all caulking must be color matched with stucco color)

SLIDING GLASS DOORS

- **Brand:** Milgard Windows & Doors
- **Series:** Trinsic Line - V300 Sliding Patio Door
- **Color:** White (all caulking must be color matched with stucco color)

SECURITY DOOR

Standard Metal



Retractable Screen



FLOORING UNDERLAY MINIMUM REQUIREMENTS

Laminate Flooring

- QuietWalk Underlayment Minimum 71 IIC and 66 STC or Similar with 71IIC and 66 STC

Tile Flooring

- Privacy Ultimate Tile/Stone Underlay™/PUU-5 Minimum Thickness 1/4"
- DURACOUSTIC S.T.O.P.™ thickness 5/16"
- Acousti-Mat® 3/8" Premium Sound Control Mat
- PROFLEX® RCU-250 Minimum Thickness 1/4"

Carpet

- Minimum 7/16" Pad